

Bodpave®

CASE STUDY



Client: **SIEMENS**
 Contractor: **Go Mow Garden Maintenance**
 Location: **Wollaton, Nottingham**
 Product: **BodPave® Grass paving grids**
 Application: **1300m² Grass car park extension**



THE PROBLEM: Additional car parking spaces were required at the clients premises in Wollaton, Nottingham. The planned location was an existing grassed area adjacent to their current full to capacity car park. The client required a reinforcement surface that kept the natural grassed finish and allowed full water penetration in-line with Sustainable Urban Drainage (SUDS) requirements and that was capable of withstanding everyday vehicular traffic.

THE SOLUTION: Boddingtons' BodPave® grass paving grids were specified as they offered a reinforcement surface capable of withstanding everyday car and van traffic whilst allowing rainwater to penetrate through into the natural sub-grade soil below. The car park was excavated and a free draining porous/open graded sub-base layer was laid as per the required design specifications. Concrete edging kerbs were constructed and the sub base was covered with a layer of blinding sand. BodPave® pavers were installed onto this surface and connected through their hook and loop connectors. The cells were filled with a soil rootzone mix and seeded. Within a few weeks the grassed surface had returned and the car park was operational within a few months.



Edging kerbs installed



Cells filled with a soil rootzone mix

CASE STUDY



Client: **SIEMENS**
 Contractor: **Go Mow Garden Maintenance**
 Location: **Wollaton, Nottingham**
 Product: **BodPave® Grass paving grids**
 Application: **1300m² Grass car park extension**

CONCLUSION: Installation took place in September 2008 and the car park was in use by December 2008 on a daily basis for regular car and van traffic. The open cell structure of BodPave® allowed full water infiltration and ensured that the grass roots could spread from cell to cell creating a strong reinforced healthy grassed surface.

BodPave® was specified due to its open cell structure, high load bearing capacity, ease of installation and economical price.



PRODUCT SPECIFICATION:

PHYSICAL CHARACTERISTICS:

Structure	Octagonal Cells
Polymer	100% recycled polyethylene
Colour	Green

NOMINAL DIMENSIONS:

Grid Size (Gross)	500mm x 500mm x 40mm (+/- 4%)
Grid Sizes laid (Nett)	483mm x 483mm x 40mm (+/- 4%)
Weight per grid	1.32kg (+/- 4%)
Weight per square metre	5.65kg

TECHNICAL CHARACTERISTICS:

Measurement	Results	Method
Resistance to compression (ambient)	150 tonnes/m ²	Internal laboratory

FURTHER ADVICE :

Contact: **Product Manager - Paul Munday**
 Telephone: +44 (0) 1709 819728
 email: paul.munday@boddingtons-ltd.com

Contact: **Technical Manager - Phil Allen**
 Telephone: +44 (0) 781 8051427
 email: phil.allen@boddingtons-ltd.com



Certificate No. FM 33039

