

## CASE STUDY



Client: Twycross Zoo  
 Location: Twycross, Atherstone  
 Contractor: Links Associates  
 Application: 6720m<sup>2</sup> Coach Parking and Vehicle Access Routes



### PROJECT RATIONALE:


Twycross Zoo has been open since 1963, attracting in excess of 450,000 visitors per year. In order to cater for this number and to increase future visitors a major refurbishment program was planned. This meant that the current visitor facilities were renewed and improved and construction on the new visitor centre was planned to start early 2009 and be finished by 2010.

The majority of the existing visitor car & coach parking facilities were in the precise location of the new visitor centre development and therefore required relocation. These new car & coach parks and their access roads were required before commencement of the new development to ensure that zoo remained open throughout.


### THE SOLUTION:

6720m<sup>2</sup> of BodPave® was specified for the heavier more regular car, coach and vehicle access routes through the park with variations on grass & gravel surfacing as dependent on application.

BodPave® paving grids were installed onto a prepared reinforced free draining crushed aggregate sub-base in line with the design specification and either filled with a gravel or rootzone for a grassed surface. BodPave® grids are designed to withstand very high loads including regular coach traffic and allow the surface to look natural (grass) whilst providing a strong reinforced surface that will not deform.



# Bodpave®



## CASE STUDY



Client: Twycross Zoo  
 Location: Twycross, Atherstone  
 Contractor: Links Associates  
 Application: 6720m<sup>2</sup> Coach Parking and Vehicle Access Routes

### THE SOLUTION CONT'D

BodPave® met the requirements of 'Source Control' conditions as part of the requirement for a SuDS application, in that the new surfaces must be able to meet with an environmental requirement to enable water to permeate either in the surface/water table and/or be carried at source to the new wetlands zone on site (Several large ponds surrounded by naturalised wetland environment) which were constructed as part of the development. This ensured that none of the surface water had to be directed into off-site drainage systems which could have had an influence of possible flash floods in the area.

BodPave® was used in conjunction with GrassProtecta® which was specified for the reinforcement of the car parking areas.



BodPave® used as the vehicle access roads

### PRODUCT SPECIFICATION:

PHYSICAL CHARACTERISTICS:	
Structure	Octagonal Cells
Polymer	100% recycled polyethylene
Colour	Green

NOMINAL DIMENSIONS:	
Grid Size (Gross)	500mm x 500mm x 40mm (+/- 4%)
Grid Sizes laid (Nett)	483mm x 483mm x 40mm (+/- 4%)
Weight per grid	1.32kg (+/- 4%)
Weight per square metre	5.65kg

TECHNICAL CHARACTERISTICS:		
Measurement	Results	Method
Resistance to compression (ambient)	150 tonnes/m <sup>2</sup>	Internal laboratory

### FURTHER ADVICE :

Contact: **Product Manager - Paul Munday**  
 Telephone: +44 (0) 1709 819728  
 email: paul.munday@boddingtons-ltd.com

Contact: **Technical Manager - Phil Allen**  
 Telephone: +44 (0) 781 8051427  
 email: phil.allen@boddingtons-ltd.com



Certificate No. FM 33039

# Bodpave®

