

SPECIFICATION SHEET



PRODUCT: FLONET™ A

PHYSICAL CHARACTERISTICS:	
STRUCTURE	Extruded Diamond Net
POLYMER	PE-HD
COLOUR	Black

DIMENSIONAL CHARACTERISTICS:	
ROLL WIDTH	2.1 m
MASS PER UNIT AREA	350 g/m ²
WEIGHT per LINEAR METRE	735 g
THICKNESS	3.9 mm
MESH COUNT	15 in 200 mm

TECHNICAL CHARACTERISTICS:			
REDUCTION in THICKNESS (at 200 kPa)	10%	EN ISO 9863	
TENSILE STRENGTH (MD)	3.5 kN/m	BS EN ISO 10319	
TENSILE STRENGTH (XD)	1.6 kN/m		
EXTENSION AT MAX LOAD (MD)	16 %		
EXTENSION AT MAX LOAD (XD)	91 %		
IN PLANE WATER FLOW @ 0.1 h.g.	20 kPa	0.25 lit/sec.m	BS EN ISO 12958
	100 kPa	0.20 lit/sec.m	
	200 kPa	0.12 lit/sec.m	
IN PLANE WATER FLOW @ 1.0 h.g.	20 kPa	1.20 lit/sec.m	
	100 kPa	1.10 lit/sec.m	
	200 kPa	1.00 lit/sec.m	

All the above information is given in good faith, but the figures are typical values only and should not be taken as a guarantee of performance. Manufacturing tolerances for dimensional and technical characteristics apply and are available on request. The company reserves the right to improve the product and adjust the specification without notice.

SPEC: FLONET A
Issue: 2
Page 1 of 1
Date: Jan 2010



Certificate No. FM 33039

BODDINGTONS LIMITED

Blackwater Trading Estate • The Causeway • Maldon • Essex CM9 4GG • England
Tel: +44 (0) 1621 874200 Fax: +44 (0) 1621 874299
e.mail: sales@boddingtons-ltd.com • www.boddingtons-ltd.com