

PRODUCT NO.: 050468


PRODUCT: CONTAMINET™ Geo-textile Mesh

| PHYSICAL CHARACTERISTICS: | |
|----------------------------------|-------------------------------------|
| GEOTEXTILE COMPOSITION | 70% Polypropylene, 30% Polyethylene |
| MESH COMPOSITION | High Density Polyethylene |
| LAMINATION | Flame Bonded |
| GEOTEXTILE COLOUR | Orange |
| MESH COLOUR | Yellow |

| DIMENSIONAL CHARACTERISTICS: | |
|-------------------------------------|----------------------|
| ROLL SIZE | 2m x 50m |
| PRODUCT THICKNESS | 4.50mm (Nominal) |
| WEIGHT | 525 g/m ² |
| ROLL WEIGHT | 52.5Kg |

| TECHNICAL CHARACTERISTICS: | | |
|--|---|-----------------|
| Measurement | Results | Test Method |
| MESH APERTURE (NOMINAL) | 28mm x 23mm | |
| TENSILE STRENGTH (kN/m) | 10.0 (MD); 8.0 (TD) | BS EN ISO 10319 |
| ELONGATION AT PEAK STRENGTH | 30% (MD); 32% (TD) | |
| CBR PUNCTURE RESISTANCE MEAN PEAK STRENGTH | 1725N | BS EN ISO 12236 |
| TRAPEZOIDAL TEAR RESISTANCE MEAN PEAK STRENGTH (GEOTEXTILE) | 300N | ASTM D4533 |
| PORE SIZE – MEAN AOS O ₉₀ (GEOTEXTILE) | 150µm | BS EN ISO 12956 |
| PERMEABILITY V _{IH50} 5cm HEAD (GEOTEXTILE) | 100 (10 ³ m.s ⁻¹ (l/m ² .s)) | BS EN ISO 11058 |

For and on behalf of boddingtons Limited



Quality Manager

All the above information is given in good faith, but the figures are typical values only and should not be taken as a guarantee of performance. Manufacturing tolerances for dimensional and technical characteristics apply and are available on request. The company reserves the right to improve the product and adjust the specification without notice.

SPEC 050468
Issue: 1
Page 1 of 1
Date: 26.4.07



Certificate No. FM 33039

BODDINGTONS LIMITED

Blackwater Trading Estate • The Causeway • Maldon • Essex CM9 4GG • England
Tel: +44 (0) 1621 874200 Fax: +44 (0) 1621 874299
e.mail: sales@boddingtons-ltd.com • www.boddingtons-ltd.com